

SPOTTED GUM

Version 2

STANDARD TRADE NAME	Spotted Gum
OTHER NAMES	Iron Gum; <i>Corymbia maculata</i>
DISTRIBUTION	Australian East Coast, South East Queensland to Northern regions of NSW.
COLOUR	The word "spotted" refers to the soft mottled colour caused by weathering of the outer tree as it sheds elliptical strips of bark. This colour varies from pale grey-browns and soft creams to a rich chocolate greeny brown in colour. Regional differences occur.
GRAIN	A frequent, wavy grain which can produce an attractive and high valued fiddleback effect. Texture moderately coarse.
DENSITY/STRENGTH	*Dry Density: 950 kg/m ³ **Janka Dry Hardness: 11 kN
DURABILITY & PROPERTIES	Hard, durable and highly resistant to decay. A very tough timber. Often treated to enhance durability of sap or transition wood.
USES	Applied and structural Flooring, Decking, Weatherboards, sleepers, bearers, board walks and the likes.

Disclaimer:

JSC has endeavoured to ensure this information is accurate but recommends that for critical applications independent advice is obtained. These properties are only a guide, as timber is a natural product there will be variations within any species.

* Air dry density (kg/m³) is average indication only and actual value may vary

** The Janka Dry Hardness rating measures the hardness of the wood. The higher the rating the harder the wood. This information may be updated at any time.

Profiles, fixing details and documentation available by request at

specification@jsctimber.co.nz

ph: 0800 572 688